



### CONSTRUCTION

<b>Available Material</b>	Polypropylene (PP) - BLACK	Polyvinylidene Fluoride (PVDF) - BLACK & NATURAL
<b>Unit Weight (with box)</b>	0.14 lbs	0.20 lbs
<b>Inlet &amp; Outlet Connections</b>	0.5" male NPT	
<b>Suction Port Cap Connection - Default (Inner Diameter)</b>	0.25" tubing barb	
<b>Suction Port Cap Connection - Alternate</b>	0.25" male NPT	
<b>Maximum Operating Temperature</b>	212°F	
<b>Maximum Operating Pressure (at 68° F)</b>	120 PSI	

### ACCESSORIES

PART NUMBER	DESCRIPTION
<b>K-184</b>	Suction line kit
<b>K-F-30L</b>	K-184 suction line kit with F-30 L liquid flowmeter
<b>K384-S</b>	K-184 suction line kit, F-30 L liquid flowmeter, and 0384 PP injector
<b>K-184-A</b>	Bypass kit (includes suction line kit K-184)
<b>K384-B</b>	K-184-A bypass kit, F-30 L liquid flowmeter, and 0384 PP injector
<b>MV-25</b>	0.25" PP metering valve with valve position indicator ring
<b>MV-25A</b>	0.25" PP metering valve
<b>S-25HB</b>	Strainer with 0.25" barbed connection

### REPLACEMENT PARTS

INJECTOR MODEL	SUCTION PORT CAP	CHECK VALVE REPAIR KIT
<b>0384 PP</b> BLACK	CAP.375 PP	CR-2
<b>0384 PVDF</b> BLACK	CAP.375 PVDF	CR-2
<b>0384 N-PVDF</b> NATURAL	CAP.375 N-PVDF	CR-2

