



Injector Data Sheet
 0584-C PP, 0584-C PVDF, & 0584-C N-PVDF

CONSTRUCTION

Available Material	Polypropylene (PP) - BLACK	Polyvinylidene Fluoride (PVDF) - BLACK & NATURAL
Unit Weight (with box)	0.14 lbs	0.19 lbs
Inlet & Outlet Connections	0.5" male NPT	
Suction Port Cap Connection - Default (Inner Diameter)	0.25" tubing barb	
Suction Port Cap Connection - Alternate	0.25" male NPT	
Maximum Operating Temperature	212°F	
Maximum Operating Pressure (at 68° F)	120 PSI	

ACCESSORIES

PART NUMBER	DESCRIPTION
K-184	Suction line kit
K-F-30L	K-184 suction line kit with F-30 L liquid flowmeter
K584C-S	K-184 suction line kit, F-30 L liquid flowmeter, and 0584-C PP injector
K-184-A	Bypass kit (includes suction line kit K-184)
K584C-B	K-184-A bypass kit, F-30 L liquid flowmeter, and 0584-C PP injector
MV-25	0.25" PP metering valve with valve position indicator ring
MV-25A	0.25" PP metering valve
S-25HB	Strainer with 0.25" barbed connection

REPLACEMENT PARTS

INJECTOR MODEL	SUCTION PORT CAP	CHECK VALVE REPAIR KIT
0584-C PP BLACK	CAP.375 PP	CR-2
0584-C PVDF BLACK	CAP .375 PVDF	CR-2
0584-C N-PVDF NATURAL	CAP.375 N-PVDF	CR-2



Model 0584-C